Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Gomastit 880
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, maintainance, services, craftsmen)

- · Product category PC1 Adhesives, sealants
- · Process category PROC11 Non industrial spraying
- · Environmental release category

ERC8c Widespread use leading to inclusion into/onto article (indoor) ERC8f Widespread use leading to inclusion into/onto article (outdoor)

- · Application of the substance / the mixture Adhesive and Sealant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

merz+benteli ag Freiburgstrasse 616

CH-3172 Niederwangen/Bern

Tel: +41 31 980 48 48 Fax: +41 31 980 48 49 E-mail: info@merz-benteli.ch Web: www.merz-benteli.ch

· Further information obtainable from:

merz+benteli ag: Tel: +41(0)31 980 48 48

E-mail: info@merz-benteli.ch

· 1.4 Emergency telephone number:

merz+benteli ag: Tel.: +41(0)31 980 48 48

National emergency phone number Switzerland: Tel.: +41 145 SwissToxicological Information center: Tel.: +41(0)44 251 51 51

E-mail: info@toxi.ch

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated

exposure.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 1)



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.
Lact.	H362	May cause harm to breast-fed children.
Aquatic Chronic 4	H413	May cause long lasting harmful effects to aquatic life.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues alkanes, C14-17, chloro

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe vapours.

P263 Avoid contact during pregnancy and while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

Contains isocyanates. May produce an allergic reaction.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119457024-46-xxxx	Diphenylmethandiisocyanat, Isomeren und Homologe Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-15%
	dimethyl ether Flam. Gas 1, H220; Press. Gas (Comp.), H280	<10%
	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
EINECS: 287-477-0	alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	2.5-<10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Take affected persons into fresh air and keep quiet.

Seek medical treatment in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Drink plenty of water. Seek medical advice immediately and show the label or packaging.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Allergic reactions

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 3)

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Foam

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

Hydrogen chloride (HCI)

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Observe the general safety regulations when handling chemicals.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool and dry location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Oct Control para	meters		
· Ingredients with	· Ingredients with limit values that require monitoring at the workplace:		
115-10-6 dimethy	yl ether		
AGW (Germany)	1900 mg/m³, 1000 ppm 8(II);DFG, EU		
75-28-5 isobutar	ne		
AGW (Germany)	2400 mg/m³, 1000 ppm 4(II);DFG		
85535-85-9 alkar	nes, C14-17, chloro		
AGW (Germany)	6 E mg/m³, 0.3 E ppm 8(II);H, Y, 11, AGS		
74-98-6 propane			
A O M / (O = 1112 = 121)	1000		

AGW (Germany) 1800 mg/m³, 1000 ppm 4(II);DFG

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

AGW (Germany) Long-term value: 0.05 E mg/m³ 1;=2=(I);DFG, H, Sah, Y, 12

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

· Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

Short term filter device:

Filter P2

(Contd. on page 6)

(Contd. of page 5)

merz+benteli ag

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

· Protection of hands:



Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.7 mm

· Penetration time of glove material

Breakthrough Time: > 480 min , Index: 6, EN 374-3

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

· **Body protection:** Light weight protective clothing recommended.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Flammability (solid, gas):

Melting point/freezing point: Not applicable

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

Ignition temperature: Not determined

· **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Not applicable.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

	(Contd. of page
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not determined.
Vapour pressure:	Not determined.
Density:	Not determined.
Relative density	0.96 g/ml (20°C / 68.0 °F)
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Reacts with water
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Solvent content:	
VOC (EC)	22.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Danger of receptacles bursting because of high vapour pressure when heated.

Forms explosive gas mixture with air.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Avoid contact with other chemicals.
- 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Product

ATE-mix, inhalation (vapour), > 5 mg/l 4h

ATE-mix, dermal, >2000 mg/kg

ATE-mix, oral, >2000 mg/kg

Components

Alkanes, C14-C17, chloro, CAS 85535-85-9

LD50, oral, rat: >2000 mg/kg

Diphenylmethanediisocyanate, isomers and homologues, CAS 9016-87-9

LD50, dermal, rabbit: >9400 mg/kg (OECD 402)

LD50, oral, rat: >10000 mg/kg (OECD 401)

LC50, inhalation (vapour), rat: 0.31 mg/l/4h (OECD 403)

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 7)

NOAEL, inhalation, rat: 0.2 mg/m3 (OECD 453) LOAEL, inhalation, rat: 1 mg/m3 (OECD 453)

Isobutane, CAS 75-28-5

LC50, inhalation, mouse: 1237 mg/l (2h) (Lit.)

Propane, CAS 74-98-6

LC50, inhalation, rat: >1443 mg/l (15 min.) (Lit.)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity

May cause harm to breast-fed children.

· STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Product

EC50, (48h), Daphnia Magna: >1000 mg/l

Alkanes, C14-C17, chloro-, CAS 85535-85-9

LC50, (96h), Fish: > 5000 mg/l (IUCLID)

EC50, (96h), Algae: > 3.2 mg/l

EC50, (48h), Daphnia magna: 0.006 mg/l NOEC, (21d), Daphnia magna: 0.01 mg/l

Diphenylmethanediisocyanate: Isomers and homologues, CAS: 9016-87-9

LC50, (96h), Danio rerio: >1000 mg/l (OECD 203)

EC50, (3h), Bacteria: >100 mg/l (OECD 209)

EC50, (24h), Daphnia magna: >1000 mg/l (OECD 202)

NOEC, (21d), Daphnia magna: >10 mg/l (OECD 202)

ErC50, (72h), Scenedesmus subspicatus: >1640 mg/l (OECD 201)

- · 12.2 Persistence and degradability No further relevant information available.
- · Other information: The product is not easily biodegradable.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 8)

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

•		
· European waste catalogue		
16 05 04*	gases in pressure containers (including halons) containing dangerous substances	
08 05 01*	waste isocyanates	
15 01 10*	packaging containing residues of or contaminated by dangerous substances	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

OFOTI					
SEC. II	ON 74.	Transport	ın	orma	ION
OLUII	OIL IT.	Hallopul		Ullia	

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- · **ADR** 1950 AEROSOLS, FLAMMABLE
- · IMDG AEROSOLS
- · IATA AEROSOLS, flammable
- · 14.3 Transport hazard class(es)
- · ADR



- Class
 Label
 2 5F Gases.
 2.1
- · IMDG, IATA



- Class
 Label
 2.1
 2.1
- · 14.4 Packing group
- · ADR, IMDG, IATA Void
- · 14.5 Environmental hazards:
- · Marine pollutant: No

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

	(Contd. of page 9
· 14.6 Special precautions for user · Hazard identification number (Kemler code)	Warning: Gases.
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	пот аррисаме.
:	
· ADR · Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D
· UN "Model Regulation":	UN1950, AEROSOLS, FLAMMABLE, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.03.2020 Version 8 Revision: 31.03.2020

Trade name: Gomastit 880

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

Lact.: Reproductive toxicity - effects on or via lactation

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

Sources Not available

· * Data compared to the previous version altered.